

ALSAN RS CLEANER

TECHNICAL DATA SHEET 230421SCANE

(supersedes 150722SCAN1E)



COMPLEMENTARY PRODUCTS

APPLICATIONS

ROOFS

BALCONIES & PLAZA-DECK

FOUNTAINS & PONDS

CIVIL ENGINEERING

FLOORING

PARKING DECKS

DESCRIPTION

ALSAN RS CLEANER is a versatile clear solvent used in the installation of SOPREMA ALSAN RS products. It is used to clean and prepare plastic and metal surfaces before the application of ALSAN RS membranes, as well as to clean tools and equipment. Additionally, it is also used to reactivate the transition surface of fully cured ALSAN RS quick-setting products.

INSTALLATION

ALSAN RS CLEANER should be applied with clean cloths or rags. If work is interrupted and the cured surface is left exposed to the elements for a period of more than 12 hours, or if it becomes dirty and contaminated, it is necessary to clean the cured surface with ALSAN RS CLEANER. After the ALSAN RS CLEANER has evaporated (approximately 15 minutes), the next layer can be applied as required.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	ALSAN RS CLEANER
Physical state	Liquid
Colour	Clear
Container	18.9 L (5.0 US Gallon)

(All values are nominal)

STORAGE AND HANDLING

Store the closed containers in a cool, ventilated, and dry place, away from any area where there is a risk of fire, and do not store them with incompatible products. Do not smoke while using ALSAN RS CLEANER. Avoid any contact with the skin and eyes during use and do not inhale the fumes.

For more information, refer to the instructions on the container label and relevant safety data sheet (SDS).



SOPREMA.US • 1.800.356.3521

SOPREMA.CA • 1.877.MAMMOUTH

TDS_ALSAN_RS_CLEANER.indd

1/1