SK 2000® FC ADHESIVE
TECHNICAL DATA SHEET

MARCH 2019

1. DESCRIPTION:

Multi-component adhesive system engineered to react chemically with specified ICC products to provide enhanced performance. Due to the special characteristics of SK-2000® FC, when used in combination with specified ICC products, spray applications are significantly easier.

All conditions being equal, the thickness achievable will be 30 - 50% greater when using SK-2000® FC at standard mixing ratios when compared to SK-13-1C. To further increase the capability of individual sprayers, a more concentrated mixture of 3:1 can be utilized at the contractors' discretion.

2. STORAGE & HANDLING:

SK-2000® FC is shipped in durable plastic drums. The drums are translucent, providing easy determination of adhesive level at the job sire on in your warehouse. The drums are marked with gallon/liter levels for further ease of use. Due to the strength of the containers, palletized drums can be stacked two levels high.

Storage temperatures are between 60°F - 95°F. SK-2000® FC becomes noticeably more viscous at temperatures below 60°F.
DO NOT ALLOW TO FREEZE.

3. PRIOR TO USE:

SK-2000® FC is a multi-component adhesive and some separation of the components during shipping and storage is expected. Consequently, thorough blending is required prior to mixing with water and use.

4. MIXING RATIOS:

STANDARD ➡ 4 Parts Water 1 Part SK-2000® FC
DURA-K ➡ 3 Parts Water 1 Part SK-2000® FC

5. ADD-ON RATE:

5 Bags/50 Gallons of Mix. Follow ICC Pressure Charts.

6. TECHNICAL SPECIFICATIONS:

UL rating when applied with specified ICC products:

FLAME SPREAD **5**
SMOKE DEVELOPMENT **5**

Wet strength is a measure of the strength of the bond shortly after application. The higher the wet strength, the easier the application. Also, the ability to spray thicker increases dramatically.

SK-2000® is a registered trademark of International Cellulose Corporation. ICC conducts continuous research and development. Specifications are subject to change without notice.

INTERNATIONAL CELLULOSE CORPORATION

12315 Robin Blvd. | Houston, TX 77045
(713) 433-6701 | Toll Free: (800) 444-1252
icc@spray-on.com | www.spray-on.com

ISO 9001 REGISTERED
Certificate NO. 6250

Distributed by SOPREMA INC.

©2019 INTERNATIONAL CELLULOSE CORPORATION. ALL RIGHTS RESERVED

TESTING AVAILABLE UPON REQUEST.